




BUJÃO DIN 910



Rosca Métrica

Rosca - Passo	D (mm)	M (mm)	L (mm)	C (mm)	S (mm)
M10X1	14,0	6,0	8,0	3,0	10,0
M12X1,5	17,0	6,0	12,0	3,0	13,0
M14X1,5	19,0	6,0	12,0	3,0	13,0
M16X1,5	21,0	6,0	12,0	3,0	17,0
M18X1,5	23,0	8,0	12,0	4,0	17,0
M20X1,5	25,0	8,0	14,0	4,0	19,0
M22X1,5	27,0	8,0	14,0	4,0	19,0
M24X1,5	29,0	9,0	14,0	4,0	22,0
M26X1,5	31,0	10,0	16,0	4,0	24,0
M30X1,5	36,0	10,0	16,0	4,0	24,0
M36X1,5	42,0	11,0	16,0	5,0	27,0

Rosca Polegada - BSP

Rosca - Fios	D (mm)	M (mm)	C (mm)	L (mm)	S (mm)
1/8-28	14,0	6,0	3,0	8,0	10,0
1/4-19	18,0	6,0	3,0	12,0	13,0
3/8-19	22,0	6,0	3,0	12,0	17,0
1/2-14	26,0	8,0	4,0	14,0	19,0
3/4-14	32,0	10,0	4,0	16,0	24,0
1''-11	39,0	11,0	5,0	16,0	27,0
1.1/4-11	49,0	12,0	5,0	16,0	30,0

1.1/2-11	55,0	12,0	5,0	16,0	30,0
----------	------	------	-----	------	------

Material	Aço Carbono
Tratamento Superficial	Oxidado
Classe de Resistência	5.8
Opções de Fornecimento	*Aço-liga com tratamento térmico *Aço Inoxidável e Latão
Fabricamos itens especiais de acordo com as suas especificações	